

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (Original) A method for enabling a user to configure a system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to configure the system, wherein the system includes one or more customizable components;

providing an image of the system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the system;

receiving customizable component selections for at least one of the one or more customizable components of the system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the system specify a configured system.

2. (Original) The method of claim 1 further comprising providing an image of the configured system to the client system for display, wherein the image of the configured system visually depicts the customizable component selections of the user.

3. (Original) The method of claim 2 wherein said providing the image of the configured system includes providing customizable component selection images corresponding to the customizable component selections of the user.

4. (Original) The method of claim 3 wherein at least a subset of the customizable component selection images are visually depicted at their respective locations on the image of the configured system.

5. (Original) The method of claim 2 wherein said providing the image of the configured system includes providing text corresponding to the customizable component selections of the user;

wherein the text is displayed in the image of the configured system.

6. (Original) The method of claim 2 wherein the image of the configured system is viewable by the user and used by the user to evaluate and confirm the customizable component selections.

7. (Original) The method of claim 2 further comprising:

receiving one or more new customizable component selections for at least one of the one or more customizable components of the configured system after said providing the image of the configured system to the client system, wherein the new customizable component selections applied to the configured system specify a new configured system;

providing an image of the new configured system, wherein the image of the new configured system visually depicts the new customizable component selections of the user.

8. (Original) The method of claim 7 wherein said receiving selections includes:

receiving user input selecting a first customizable component;

providing a menu of possible options for the first customizable component to the client system for display after the user input selecting the first customizable component;

receiving user input selecting one of the possible options for the first customizable component.

9. (Original) The method of claim 1 wherein said receiving user input selecting the image of the first customizable component further includes:

receiving user input indicating that a position of a cursor of the client system overlaps a location of the image of the first customizable component displayed in the image of the system.

10. (Original) The method of claim 1 wherein said receiving customizable component selections further includes:

providing a menu comprising customizable component options of the first customizable component for display on the client system after said receiving user input selecting the image of the first customizable component.

11. (Original) The method of claim 10 wherein the menu comprising the customizable component options includes text indicating the customizable component options.

12. (Original) The method of claim 10 wherein the menu comprising the customizable component options includes images indicating the customizable component options.

13. (Original) The method of claim 10 wherein the menu is operable to be displayed proximate to the location of the image of the first customizable component

14. (Original) The method of claim 10 wherein said receiving customizable component selections further includes:

providing a sequence of images corresponding to the customizable component options of the first customizable component after said receiving user input selecting the image of the first customizable component.

15. (Original) The method of claim 10 wherein said receiving user input selecting the first customizable component option includes:

providing customizable component option images corresponding to the customizable component options of the first customizable component;

receiving user input selecting a first customizable component option image corresponding to the first customizable component option.

16. (Original) The method of claim 1 further comprising:

providing an image of the first customizable component option for display on the client system in response to said receiving user input selecting the first customizable component option for the first customizable component.

17. (Original) A method for enabling a user to configure a measurement system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to configure the measurement system, wherein the measurement system includes one or more customizable components, wherein at least one of the customizable components is a measurement device;

providing an image of the measurement system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the measurement system;

receiving customizable component selections for at least one of the one or more customizable components of the measurement system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the measurement system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the measurement system specify a configured measurement system.

18. (Original) The method of claim 17 further comprising providing an image of the configured measurement system to the client system for display, wherein the image of the configured measurement system visually depicts the customizable component selections of the user.

19. (Original) The method of claim 18 wherein said providing the image of the configured measurement system includes providing customizable component selection images corresponding to the customizable component selections of the user.

20. (Original) The method of claim 19 wherein at least a subset of the customizable component selection images are visually depicted at their respective locations on the image of the configured measurement system.

21. (Original) The method of claim 18 wherein said providing the image of the configured measurement system includes providing text corresponding to the customizable component selections of the user;

wherein the text is displayed in the image of the configured measurement system.

22. (Original) The method of claim 18 wherein the image of the configured measurement system is viewable by the user and used by the user to evaluate and confirm the customizable component selections.

23. (Original) The method of claim 18 further comprising:

receiving one or more new customizable component selections for at least one of the one or more customizable components of the configured measurement system after said providing the image of the configured measurement system to the client system, wherein the new customizable component selections applied to the configured measurement system specify a new configured measurement system;

providing an image of the new configured measurement system, wherein the image of the new configured measurement system visually depicts the new customizable component selections of the user.

24. (Original) The method of claim 23 wherein said receiving selections includes:

receiving user input selecting a first customizable component;

providing a menu of possible options for the first customizable component to the client system for display after the user input selecting the first customizable component;

receiving user input selecting one of the possible options for the first customizable component.

25. (Original) The method of claim 17 wherein said receiving user input selecting the image of the first customizable component further includes:

receiving user input indicating that a position of a cursor of the client system overlaps a location of the image of the first customizable component displayed in the image of the measurement system.

26. (Original) The method of claim 17 wherein said receiving customizable component selections further includes:

providing a menu comprising customizable component options of the first customizable component for display on the client system after said receiving user input selecting the image of the first customizable component.

27. (Original) The method of claim 26 wherein the menu comprising the customizable component options includes text indicating the customizable component options.

28. (Original) The method of claim 26 wherein the menu comprising the customizable component options includes images indicating the customizable component options.

29. (Original) The method of claim 26 wherein the menu is operable to be displayed proximate to the location of the image of the first customizable component

30. (Original) The method of claim 26 wherein said receiving customizable component selections further includes:

providing a sequence of images corresponding to the customizable component options of the first customizable component after said receiving user input selecting the image of the first customizable component.

31. (Original) The method of claim 26 wherein said receiving user input selecting the first customizable component option includes:

providing customizable component option images corresponding to the customizable component options of the first customizable component;

receiving user input selecting a first customizable component option image corresponding to the first customizable component option.

32. (Original) The method of claim 17 further comprising:

providing an image of the first customizable component option for display on the client system in response to said receiving user input selecting the first customizable component option for the first customizable component.

33. (Original) A method for enabling a user to configure a computer system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, the method comprising:

receiving a request from a user of the client system to configure the computer system, wherein the computer system includes one or more customizable components, wherein at least one of the customizable components is an electronic device;

providing an image of the computer system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the computer system;

receiving customizable component selections for at least one of the one or more customizable components of the computer system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the computer system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the computer system specify a configured computer system.

34. (Original) The method of claim 33 further comprising providing an image of the configured computer system to the client system for display, wherein the image of the configured computer system visually depicts the customizable component selections of the user.

35. (Original) The method of claim 34 wherein said providing the image of the configured computer system includes providing customizable component selection images corresponding to the customizable component selections of the user.



36. (Original) The method of claim 35 wherein at least a subset of the customizable component selection images are visually depicted at their respective locations on the image of the configured computer system.

37. (Original) The method of claim 34 wherein said providing the image of the configured computer system includes providing text corresponding to the customizable component selections of the user;

wherein the text is displayed in the image of the configured computer system.

38. (Original) The method of claim 34 wherein the image of the configured computer system is viewable by the user and used by the user to evaluate and confirm the customizable component selections.

39. (Original) The method of claim 34 further comprising:

receiving one or more new customizable component selections for at least one of the one or more customizable components of the configured computer system after said providing the image of the configured computer system to the client system, wherein the new customizable component selections applied to the configured computer system specify a new configured computer system;

providing an image of the new configured computer system, wherein the image of the new configured computer system visually depicts the new customizable component selections of the user.

40. (Original) The method of claim 39 wherein said receiving selections includes:

receiving user input selecting a first customizable component;

providing a menu of possible options for the first customizable component to the client system for display after the user input selecting the first customizable component;

receiving user input selecting one of the possible options for the first customizable component.

41. (Original) The method of claim 33 wherein said receiving user input selecting the image of the first customizable component further includes:

receiving user input indicating that a position of a cursor of the client system overlaps a location of the image of the first customizable component displayed in the image of the computer system.

42. (Original) The method of claim 33 wherein said receiving customizable component selections further includes:

providing a menu comprising customizable component options of the first customizable component for display on the client system after said receiving user input selecting the image of the first customizable component.

43. (Original) The method of claim 42 wherein the menu comprising the customizable component options includes text indicating the customizable component options.

44. (Original) The method of claim 42 wherein the menu comprising the customizable component options includes images indicating the customizable component options.

45. (Original) The method of claim 42 wherein the menu is operable to be displayed proximate to the location of the image of the first customizable component

46. (Original) The method of claim 42 wherein said receiving customizable component selections further includes:

providing a sequence of images corresponding to the customizable component options of the first customizable component after said receiving user input selecting the image of the first customizable component.

47. (Original) The method of claim 42 wherein said receiving user input selecting the first customizable component option includes:

providing customizable component option images corresponding to the customizable component options of the first customizable component;

receiving user input selecting a first customizable component option image corresponding to the first customizable component option.

48. (Original) The method of claim 33 further comprising:

providing an image of the first customizable component option for display on the client system in response to said receiving user input selecting the first customizable component option for the first customizable component.

49. (Original) A memory medium comprising program instructions for enabling a user to configure a system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, wherein the program instructions are executable to implement:

receiving a request from a user of the client system to configure the system, wherein the system includes one or more customizable components;

providing an image of the system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the system;

receiving customizable component selections for at least one of the one or more customizable components of the system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the system specify a configured system.

50. (Original) A memory medium comprising program instructions for enabling a user to configure a computer system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, wherein the program instructions are executable to implement:

receiving a request from a user of the client system to configure the computer system, wherein the computer system includes one or more customizable components, wherein at least one of the customizable components is an electronic device;

providing an image of the computer system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the computer system;

receiving customizable component selections for at least one of the one or more customizable components of the computer system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the computer system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the computer system specify a configured computer system.

51. (Original) A memory medium comprising program instructions for enabling a user to configure a measurement system in an e-commerce system, wherein the e-commerce system includes a client system coupled through a network to an electronic commerce server, wherein the program instructions are executable to implement:

receiving a request from a user of the client system to configure the measurement system, wherein the measurement system includes one or more customizable components, wherein at least one of the customizable components is a measurement device;

providing an image of the measurement system to the client system for display, wherein images of at least a subset of the one or more customizable components form at least a portion of the image of the measurement system;

receiving customizable component selections for at least one of the one or more customizable components of the measurement system in response to user input, wherein said receiving customizable component selections comprises:

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the measurement system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first customizable component option for the first customizable component, wherein the user input selecting the first customizable component option comprises the customizable component selection for the first customizable component;

wherein the customizable component selections applied to the measurement system specify a configured measurement system.

52. (New) A method for configuring a system in an e-commerce system, wherein the e-commerce system includes a server computer coupled through a network to a client computer, the method comprising:

providing an image of a system to the client computer for display, wherein the image of the system comprises images of one or more customizable components;

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first option for the first customizable component,  
wherein the first option comprises the selection for the first customizable component;  
wherein one or more selections specify a configured system.

53. (New) The method of claim 52, further comprising:

providing a menu comprising options of the first customizable component for display on the client computer after said receiving user input selecting the image of the first customizable component.

54. (New) The method of claim 52, wherein said receiving user input selecting the first option comprises:

providing images corresponding to options of the first customizable component;  
receiving user input selecting a first image corresponding to the first option.

55. (New) The method of claim 52, further comprising:

providing an image of the first option for display on the client computer in response to said receiving user input selecting the option for the first customizable component.

56. (New) The method of claim 52, further comprising:

providing an image of the configured system to the client computer for display, wherein the image of the configured system visually depicts the one or more selections of the user.

57. (New) The method of claim 52, further comprising:

receiving payment information for the configured system to purchase the configured system.

58. (New) The method of claim 57, further comprising:

providing the configured system to a user of the client computer after said receiving payment information for the configured system to purchase the configured system.

59 (New) The method of claim 52, where the system is a measurement system.

60. (New) The method of claim 52, where the system is a computer system.

61. (New) The method of claim 52, where the system comprises a plurality of electronic devices.

62. (New) A method for configuring a measurement system in an e-commerce system, wherein the e-commerce system includes a server computer coupled through a network to a client computer, the method comprising:

providing an image of a measurement system to the client computer for display, wherein the image of the measurement system comprises images of one or more customizable components, wherein at least one of the customizable components is a measurement device;

receiving user input selecting an image of the measurement device which is visually depicted in the image of the measurement system, wherein said receiving user input selecting the image of the measurement device operates to select the measurement device for configuration; and

receiving user input selecting a first option for the measurement device, wherein the first option comprises the selection for the measurement device;

wherein one or selections specify a configured measurement system.

63. (New) The method of claim 62, further comprising:

providing a menu comprising options for the measurement device for display on the client computer after said receiving user input selecting the image of the measurement device.

64. (New) The method of claim 62, wherein said receiving user input selecting the first option includes:

providing images corresponding to the options of the measurement device;  
receiving user input selecting a first image corresponding to the first option.

65. (New) The method of claim 62, further comprising:

providing an image of the first option for display on the client computer in response to said receiving user input selecting the first option for the measurement device.

66. (New) The method of claim 62, further comprising:

providing an image of the configured measurement system to the client computer for display, wherein the image of the configured measurement system visually depicts the one or more selections of the user.

67. (New) The method of claim 62, further comprising:

receiving payment information for the configured measurement system to purchase the configured measurement system.

68. (New) The method of claim 67, further comprising:

providing the configured measurement system to a user of the client computer after said receiving payment information for the configured measurement system to purchase the configured measurement system.

69. (New) A method for configuring a computer system in an e-commerce system, wherein the e-commerce system includes a server computer coupled through a network to a client computer, the method comprising:



providing an image of a computer system to the client computer for display, wherein the image of the computer system comprises images of one or more customizable components;

receiving user input selecting an image of a first customizable component which is visually depicted in the image of the computer system, wherein said receiving user input selecting the image of the first customizable component operates to select the first customizable component for configuration; and

receiving user input selecting a first option for the first customizable component, wherein the first option is the selection for the first customizable component; wherein one or more selections specify a configured computer system.

70. (New) The method of claim 69, further comprising:

providing a menu comprising options for the customizable component for display on the client computer after said receiving user input selecting the image of the customizable component.

61. (New) The method of claim 69, wherein said receiving user input selecting the first option includes:

providing images corresponding to the options of the first customizable component; and

receiving user input selecting a first image corresponding to the first option.

72. (New) The method of claim 69, further comprising:

providing an image of the first option for display on the client computer in response to said receiving user input selecting the first option for the first customizable component.

73. (New) The method of claim 69, further comprising:

providing an image of the configured measurement system to the client computer for display, wherein the image of the configured computer system visually depicts the one or more selections of the user.

74. (New) The method of claim 69, further comprising:  
receiving payment information for the configured computer system to purchase  
the configured computer system.

75. (New) The method of claim 74, further comprising:  
providing the configured computer system to a user of the client computer after  
said receiving payment information for the configured computer system to purchase the  
configured computer system.